



特 性

- 最大功率可達 320KW
- 最高達 8 台主/從並聯控制
- 5位數之數位電壓、電流以及功率錶
- 高速量測及通訊傳輸速率
- 大型 LCD Display、可用飛梭旋鈕或按鍵調整設定值
- 可同時顯示電壓值、電流值、瓦特值
- 適用於功率因數調整器(PFC)測試用 (600V,1000V機種)
- 可自動執行OCP、OPP測試
- 可設定開機狀態值
- 定電流、定電阻、定電壓、定功率、定電流+定電壓、定功率+定電壓、動態及短路模式
- 於短路測試時可設定短路時間
- 過電流、功率、溫度保護及過電壓示警
- 電壓極性顯示可設成正值 (“+”) 或負值 (“-”)
- 支援太陽能板MPPT CC、CR、CV測試
- 可選用介面：GPIO、RS232、USB、LAN

說 明

- 34000A系列具有獨立的控制及顯示面板、定電流/定電阻/定電壓/定功率/動態模式，配合面板上的150組 儲存/呼叫 記憶，能有效地控制所有負載的設定，更可透過RS232、Ethernet、USB和GPIO等介面進行遠端控制。
- 具備短路測試功能及設定短路時間，並可量測短路電壓及電流。
- 在定電流及定功率模式下，可做動態負載之模擬，其電流上升、下降斜率均為獨立可調，另具有-外部輸入任意波形之動態負載功能。
- 具有OCP、OPP單鍵測試功能，使得OCP、OPP之測試更有效率及準確。
- 可設定的吃載/停止吃載(Load ON/OFF)電壓點及良/不良(GO/NG)的比較判斷功能、電壓極性顯示可正可負及150組 儲存/呼叫 記憶，使得負載更適用於各種不同的應用。
- 多達150組測試參數及狀態的儲存功能，讓其可根據自動測試 (auto sequence) 需求，隨時將儲存記憶調出來任意使用。
- 因其耐壓可高達1000V，故而非常適用於功率因數調整器 (PFC) 的測試應用。
- 主/從控制最多為1個MASTER，7個SLAVE

應 用

- 電壓/電流源測試
- 交換式電源供應器暫態響應
- 定電壓模式供限流測試及模擬電池
- 電池放電
- 電池充電
- 研發、品管
- ATE系統
- 生產測試

規 格

MODEL	34105A		34110A		34115A		34120A		34125A	
Power	5KW		10KW		15KW		20KW		25KW	
Current	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A
Voltage	0 ~ 60V		0 ~ 60V		0 ~ 60V		0 ~ 60V		0 ~ 60V	
Min. Operating Voltage	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³
Protections										
Over Power Protection (OPP)	105%									
Over Current Protection (OCP)	104%									
Over Voltage Protection (OVP)	105%									
Over Temp Protection (OTP)	Yes									
Constant Current Mode										
Range ¹	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA
Accuracy	± (0.1% of Setting + 0.2% of Range)									
Constant Resistance Mode										
Range	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω
Resolution	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ
Accuracy	± 0.2% of (Setting + Range)									
Constant Voltage Mode										
Range	60V									
Resolution	1mV									
Accuracy	± 0.05% of (Setting + Range)									
Constant Power Mode										
Range	500W	5000W	1000W	10000W	1500W	15000W	2000W	20000W	2500W	25000W
Resolution	8mW	80mW	16mW	160mW	24mW	240mW	32mW	320mW	40mW	400mW
Accuracy	± 0.5% of (Setting + Range)									
Constant Voltage Mode + Constant Current Mode										
Range	60V	1000A	60V	1000A	60V	1000A	60V	1000A	60V	1000A
Resolution	1mV	16mA	1mV	16mA	1mV	16mA	1mV	16mA	1mV	16mA
Accuracy	± 1.0% of (Setting + Range)									
Constant Voltage Mode + Constant Power Mode										
Range	60V	5000W	60V	10000W	60V	15000W	60V	20000W	60V	25000W
Resolution	1mV	80mW	1mV	160mW	1mV	240mW	1mV	320mW	1mV	400mW
Accuracy	± 1.0% of (Setting + Range)									
MPPT Mode										
Algorithm	P&O + Scanning									
Load mode	CC, CR, CV (MPPT C, R, V)									
Sampling interval	10ms~2000ms ; resolution 1ms									
P&O interval	10ms~2000ms ; resolution 1ms									
Memory situation	Discard old data and keep catching new data									
Dynamic Mode										
Timing										
Thigh & Tlow	0.150~9.999 / 99.99 / 999.9 / 9999ms									
Resolution	0.001 / 0.01 / 0.1 / 1ms									
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm									
Slew Rate	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs
Resolution	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs
Min. Rise Time	66.7μs(typical)									
Current										
Range	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA
Measurement										
Voltage Read Back										
Range (5 Digital)	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V
Resolution	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV
Accuracy	± 0.025% of (Reading + Range)									
Current Read Back										
Range (5 Digital)	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA
Accuracy	± 0.1% of (Reading + Range)									
Power Read Back										
Range (5 Digital)	1000W	5000W	1000W	10000W	10000W	15000W	10000W	20000W	10000W	25000W
Resolution	0.01W	0.1W	0.01W	1W	0.1W	1W	0.1W	1W	0.1W	1W
Accuracy	± 0.125% of (Reading + Range)									
General										
Short Circuit										
Current	1000A									
Load ON Voltage										
Current	0.1~25V									
Load OFF Voltage										
Current	0~25V									
Power Consumption										
34105A	600Wmax		1000Wmax		1450Wmax		1900Wmax		2350Wmax	
Operating Temperature²										
Temperature	0~40°C									
Dimension (HxWxD)										
34105A	573x647x766mm		573x647x766mm		728x647x766mm		885x647x766mm		1041x647x766mm	
HxWxD (Not included wheels)										
34105A	469x647x766mm		469x647x766mm		625x647x766mm		781x647x766mm		937x647x766mm	
Weight										
34105A	100 Kg		130 kg		170 kg		220 kg		280 kg	
Safety & EMC										
CE										

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含) : 100~230 Vac ±10%, 50/60Hz
 ② Load-25KW以上(含) : 200~230 Vac ±10%, 50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

選購配件：

吊環



34105A 60V,1000A,5KW



34110A 60V,1000A,10KW



34115A 60V,1000A,15KW



34120A 60V,1000A,20KW



34125A 60V, 1000A, 25KW



規 格

MODEL	34130A		34135A		34140A		34205A		34210A	
Power	30KW		35KW		40KW		5KW		10KW	
Current	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0 ~ 16A	0 ~ 160A	0 ~ 32A	0 ~ 320A
Voltage	0 ~ 60V									
Min. Operating Voltage	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	0.1V@100A	0.7V@1000A ³	10V@160A		10V@320A	
Protections										
Over Power Protection (OPP)	105%									
Over Current Protection (OCP)	104%									
Over Voltage Protection (OVP)	105%									
Over Temp Protection (OTP)	Yes									
Constant Current Mode										
Range ¹	0~100A	0~1000A	0~100A	0~1000A	0~100A	0~1000A	0 ~ 16A	0 ~ 160A	32A	320A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	0.256mA	2.56mA	0.512mA	5.12mA
Accuracy	± (0.1% of Setting + 0.2% of Range)									
Constant Resistance Mode										
Range	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	3600Ω~0.06Ω	0.06Ω~0.001Ω	15000Ω~3.75Ω	3.75Ω~0.063Ω	12500Ω~1.875Ω	1.875Ω~0.0315Ω
Resolution	277μS	0.001mΩ	277μS	0.001mΩ	277μS	0.001mΩ	4.4μS	63μΩ	8.8μΩ	0.0315mΩ
Accuracy	± 0.2% of (Setting + Range)									
Constant Voltage Mode										
Range	60V						600V			
Resolution	1mV						10mV			
Accuracy	± 0.05% of (Setting + Range)									
Constant Power Mode										
Range	3000W	30000W	3500W	35000W	4000W	40000W	500W	5000W	1000W	10000W
Resolution	48mW	480mW	56mW	560mW	64mW	640mW	8mW	80mW	16mW	160mW
Accuracy	± 0.5% of (Setting + Range)									
Constant Voltage Mode + Constant Current Mode										
Range	60V	1000A	60V	1000A	60V	1000A	600V	160A	600V	320A
Resolution	1mV	16mA	1mV	16mA	1mV	16mA	10mV	2.56mA	10mV	5.12mA
Accuracy	± 1.0% of (Setting + Range)									
Constant Voltage Mode + Constant Power Mode										
Range	60V	30000W	60V	35000W	60V	40000W	600V	5000W	600V	10000W
Resolution	1mV	480mW	1mV	560mW	1mV	640mW	10mV	80mW	10mV	160mW
Accuracy	± 1.0% of (Setting + Range)									
MPPT Mode										
Algorithm	P&O + Scanning									
Load mode	CC, CR, CV (MPPT C, R, V)									
Sampling interval	10ms~2000ms ; resolution 1ms									
P&O interval	10ms~2000ms ; resolution 1ms									
Memory situation	Discard old data and keep catching new data									
Dynamic Mode										
Timing										
Thigh & Tlow	0.150~9.999 / 99.99 / 999.9 / 9999ms									
Resolution	0.001 / 0.01 / 0.1 / 1ms									
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm									
Slew Rate	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	24mA~1.5A/μs	240mA~15A/μs	12.8mA~800mA/μs	128mA~8A/μs	25.6mA~1.6A/μs	256mA~16A/μs
Resolution	6mA/μs	60mA/μs	6mA/μs	60mA/μs	6mA/μs	60mA/μs	3.2mA/μs	32mA/μs	6.4mA/μs	64mA/μs
Min. Rise Time	66.7μs(typical)						20μs(typical)			
Current										
Range	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~16A	16~160A	0~32A	32~320A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	0.256mA	2.56mA	0.512mA	5.12mA
Measurement										
Voltage Read Back										
Range (5 Digital)	0~6V	6~60V	0~6V	6~60V	0~6V	6~60V	0~60V	60~600V	0~60V	60~600V
Resolution	0.1mV	1mV	0.1mV	1mV	0.1mV	1mV	1mV	10mV	1mV	10mV
Accuracy	± 0.025% of (Reading + Range)									
Current Read Back										
Range (5 Digital)	0~100A	100~1000A	0~100A	100~1000A	0~100A	100~1000A	0~16A	16~160A	0~32A	32~320A
Resolution	1.6mA	16mA	1.6mA	16mA	1.6mA	16mA	0.256mA	2.56mA	0.512mA	5.12mA
Accuracy	± 0.1% of (Reading + Range)									
Power Read Back										
Range (5 Digital)	10000W	30000W	10000W	35000W	10000W	40000W	1000W	5000W	1000W	10000W
Resolution	0.1W	1W	0.1W	1W	0.1W	1W	0.01W	0.1W	0.01W	1W
Accuracy	± 0.125% of (Reading + Range)									
General										
Short Circuit										
Current	1000A						160A		320A	
Load ON Voltage	0.1~25V						0.4 ~ 100V		0.4 ~ 100V	
Load OFF Voltage	0~25V						0 ~ 100V			
Power Consumption	2800Wmax		3250Wmax		3700Wmax		600Wmax		1000Wmax	
Operating Temperature ²	0~40°C									
Dimension (HxWxD)	1197x647x766mm		1353x647x766mm		1509x647x766mm		573x647x766mm		573x647x766mm	
HxWxD (Not included wheels)	1093x647x766mm		1249x647x766mm		1405x647x766mm		469x647x766mm		469x647x766mm	
Weight	340 Kg		390 kg		430 kg		100 kg		130 kg	
Safety & EMC	CE									

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz
 ② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面： 選購配件：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card



規 格

MODEL	34215A		34220A		34225A		34230A		34235A		
Power	15KW		20KW		25KW		30KW		35KW		
Current	0 ~ 48A	0 ~ 480A	0 ~ 64A	0 ~ 640A	0 ~ 80A	0 ~ 800A	0 ~ 96A	0 ~ 960A	0 ~ 112A	0 ~ 1120A	
Voltage					0 ~ 600V						
Min. Operating Voltage	10V @ 480A		10V @ 640A		10V @ 800A		10V @ 960A		10V @ 1120A		
Protections											
Over Power Protection (OPP)					105%				105%		
Over Current Protection (OCP)					105%				104%		
Over Voltage Protection (OVP)					105%				105%		
Over Temp Protection (OTP)					Yes				Yes		
Constant Current Mode											
Range ¹	48A	480A	64A	640A	80A	800A	96A	960A	112A	1120A	
Resolution	0.768mA	7.68mA	1.024mA	10.24mA	1.28mA	12.8mA	1.536mA	15.36mA	1.792mA	17.92mA	
Accuracy	± (0.1% of Setting + 0.2% of Range)										
Constant Resistance Mode											
Range	1500Ω~1.25Ω	1.25Ω~0.021Ω	11250Ω~0.9375Ω	0.9375Ω~0.01575Ω	11250Ω~0.75Ω	0.75Ω~0.0126Ω	12500Ω~0.625Ω	0.625Ω~0.0105Ω	6428.4Ω~0.5357Ω	0.5357Ω~0.009Ω	
Resolution	13.3μs	0.021mΩ	17.7μs	0.01575mΩ	22.2μs	0.0126mΩ	26.6μs	0.0105mΩ	31.1μs	0.009mΩ	
Accuracy	±0.2% of (Setting + Range)										
Constant Voltage Mode											
Range	600V										
Resolution	10mV										
Accuracy	± 0.05% of (Setting + Range)										
Constant Power Mode											
Range	1500W	15000W	2000W	20000W	2500W	25000W	3000W	30000W	3500W	35000W	
Resolution	24mW	240mW	32mW	320mW	40mW	400mW	48mW	480mW	56mW	560mW	
Accuracy	± 0.5% of (Setting + Range)										
Constant Voltage Mode + Constant Current Mode											
Range	600V	480A	600V	640A	600V	800A	600V	960A	600V	1120A	
Resolution	10mV	7.68mA	10mV	10.24mA	10mV	12.8mA	10mV	15.36mA	10mV	17.92mA	
Accuracy	± 1.0% of (Setting + Range)										
Constant Voltage Mode + Constant Power Mode											
Range	600V	15000W	600V	20000W	600V	25000W	600V	30000W	600V	35000W	
Resolution	10mV	240mW	10mV	320mW	10mV	400mW	10mV	480mW	10mV	560mW	
Accuracy	± 1.0% of (Setting + Range)										
MPPT Mode											
Algorithm	P&O + Scanning										
Load mode	CC, CR, CV (MPPT C, R, V)										
Sampling interval	10ms~2000ms ; resolution 1ms										
P&O interval	10ms~2000ms ; resolution 1ms										
Memory situation	Discard old data and keep catching new data										
Dynamic Mode											
Timing											
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999ms										
Resolution	0.001 / 0.01 / 0.1 / 1ms										
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm										
Slew Rate	38.4mA~2.4A/μs	384mA~24A/μs	51.2mA~3.2A/μs	512mA~32A/μs	64mA~4A/μs	640mA~40A/μs	76.8mA~4.8A/μs	768mA~48A/μs	0.0896A~5.6A/μs	0.896A~56A/μs	
Resolution	9.6mA/μs	96mA/μs	12.8mA/μs	128mA/μs	16mA/μs	160mA/μs	19.2mA/μs	192mA/μs	22.4mA/μs	224mA/μs	
Min. Rise Time	20μs(typical)										
Current											
Range	0~48A	48~480A	0~64A	64~640A	0~80A	80~800A	0~96A	96~960A	0~112A	112~1120A	
Resolution	0.768mA	7.68mA	1.024mA	10.24mA	1.28mA	12.8mA	1.536mA	15.36mA	1.792mA	17.92mA	
Measurement											
Voltage Read Back											
Range (5 Digital)	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	
Resolution	1mV	10mV	1mV	10mV	1mV	10mV	1mV	10mV	1mV	10mV	
Accuracy	±0.025% of (Reading + Range)										
Current Read Back											
Range (5 Digital)	0~48A	48~480A	0~64A	64~640A	0~80A	80~800A	0~96A	96~960A	0~112A	112~1120A	
Resolution	0.768mA	7.68mA	1.024mA	10.24mA	1.28mA	12.8mA	1.536mA	15.36mA	1.792mA	17.92mA	
Accuracy	±0.1% of (Reading + Range)										
Power Read Back											
Range (5 Digital)	10000W	15000W	10000W	20000W	10000W	25000W	10000W	30000W	10000W	35000W	
Resolution	0.1W	1W	0.1W	1W	0.1W	1W	0.1W	1W	0.1W	1W	
Accuracy	±0.125% of (Reading + Range)										
General											
Short Circuit											
Current	480A		640A		800A		960A		1120A		
Load ON Voltage	0.4 ~ 100V										
Load OFF Voltage	0 ~ 100V										
Power Consumption	1450Wmax		1900Wmax		2350Wmax		2800Wmax		3250Wmax		
Operating Temperature ²	0~40°C										
Dimension (HxWxD)	728x647x766mm		885x647x766mm		1041x647x766mm		1197x647x766mm		1353x647x766mm		
HxWxD (Not included wheels)	625x647x766mm		781x647x766mm		937x647x766mm		1093x647x766mm		1249x647x766mm		
Weight	170 kg		220 kg		280 kg		340 kg		390 kg		
Safety & EMC	CE										

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz
 ② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面： 選購配件：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card



34215A 600V,480A,15KW 34220A 600V,640A,20KW 34225A 600V,800A,25KW 34230A 600V,960A,30KW 34235A 600V,1120A,35KW

規 格

MODEL	34240A		34305A		34310A		34315A		34320A	
Power	40KW		5KW		10KW		15KW		20KW	
Current	0 ~ 128A 0 ~ 1280A		0 ~ 5A 0 ~ 50A		0 ~ 10A 0 ~ 100A		0 ~ 15A 0 ~ 150A		0 ~ 20A 0 ~ 200A	
Voltage	0 ~ 600V				0 ~ 1000V					
Min. Operating Voltage	10V @ 1280A		10V @ 50A		10V @ 100A		10V @ 150A		10V @ 200A	
Protections										
Over Power Protection (OPP)	105%						105%			
Over Current Protection (OCP)	104%						104%			
Over Voltage Protection (OVP)	105%						104%			
Over Temp Protection (OTP)	Yes						Yes			
Constant Current Mode										
Range ^{*1}	128A	1280A	5A	50A	10A	100A	15A	150A	20A	200A
Resolution	2.048mA	20.48mA	0.08mA	0.8mA	0.16mA	1.6mA	0.24mA	2.4mA	0.32mA	3.2mA
Accuracy	± (0.1% of Setting + 0.2% of Range)									
Constant Resistance Mode										
Range	5625Ω ~ 0.46875Ω	0.46875Ω ~ 0.00787Ω	24000Ω ~ 20Ω	20Ω ~ 0.2004Ω	12000Ω ~ 10Ω	10Ω ~ 0.1002Ω	8332.5Ω ~ 6.666Ω	6.6659Ω ~ 0.066792Ω	6000Ω ~ 5Ω	5Ω ~ 0.0501Ω
Resolution	35.5μS	0.007875mΩ	0.833μS	0.334mΩ	1.666μS	0.167mΩ	2.4μS	0.11132mΩ	3.33μS	0.0835mΩ
Accuracy	±0.2% of (Setting + Range)									
Constant Voltage Mode										
Range	600V				10 ~ 1000V					
Resolution	10mV				16mV					
Accuracy	± 0.05% of (Setting + Range)									
Constant Power Mode										
Range	4000W	40000W	500W	5000W	1000W	10000W	1500W	15000W	2000W	20000W
Resolution	64mW	640mW	8mV	80mW	16mV	160mW	24mW	240mW	32mW	320mW
Accuracy	± 0.5% of (Setting + Range)									
Constant Voltage Mode + Constant Current Mode										
Range	600V	1280A	1000V	50A	1000V	100A	1000V	150A	1000V	200A
Resolution	10mV	20.48mA	16mV	0.8mA	16mV	1.6mA	16mV	2.4mA	16mV	3.2mA
Accuracy	± 1.0% of (Setting + Range)									
Constant Voltage Mode + Constant Power Mode										
Range	600V	40000W	1000V	5000W	1000V	10000W	1000V	15000W	1000V	20000W
Resolution	10mV	640mW	16mV	80mW	16mV	160mW	16mV	240mW	16mV	320mW
Accuracy	± 1.0% of (Setting + Range)									
MPPT Mode										
Algorithm	P&O + Scanning									
Load mode	CC, CR, CV (MPPT C, R, V)									
Sampling interval	10ms~2000ms ; resolution 1ms									
P&O interval	10ms~2000ms ; resolution 1ms									
Memory situation	Discard old data and keep catching new data									
Dynamic Mode										
Timing										
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999ms									
Resolution	0.001 / 0.01 / 0.1 / 1ms									
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm									
Slew Rate	0.1024A~6.4A/μs	1.024A~64A/μs	0.004A~0.25A/μs	0.04A~2.5A/μs	0.008A~0.5A/μs	0.08A~5A/μs	0.012A~0.75A/μs	0.12A~7.5A/μs	0.016A~1A/μs	0.16A~10A/μs
Resolution	25.6mA/μs	256mA/μs	0.001A/μs	0.01A/μs	0.002A/μs	0.02A/μs	0.003A/μs	0.03A/μs	0.004A/μs	0.04A/μs
Min. Rise Time	20μs(typical)									
Current										
Range	0~128A	128~1280A	0~5A	5~50A	0~10A	10~100A	0~15A	15~150A	0~20A	20~200A
Resolution	2.048mA	20.48mA	0.08mA	0.8mA	0.16mA	1.6mA	0.24mA	2.4mA	0.32mA	3.2mA
Measurement										
Voltage Read Back										
Range (5 Digital)	0~60V	60~600V	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V
Resolution	1mV	10mV	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV
Accuracy	±0.025% of (Reading + Range)									
Current Read Back										
Range (5 Digital)	0~128A	128~1280A	0~5A	5~50A	0~10A	10~100A	0~15A	15~150A	0~20A	20~200A
Resolution	2.048mA	20.48mA	0.08mA	0.8mA	0.16mA	1.6mA	0.24mA	2.4mA	0.32mA	3.2mA
Accuracy	±0.1% of (Reading + Range)									
Power Read Back										
Range (5 Digital)	10000W	40000W	1000W	5000W	1000W	10000W	10000W	15000W	10000W	20000W
Resolution	0.1W	1W	0.01W	0.1W	0.01W	1W	0.1W	1W	0.1W	1W
Accuracy	±0.125% of (Reading + Range)									
General										
Short Circuit										
Current	1280A		50A		100A		150A		200A	
Load ON Voltage	0.4 ~ 100V				10.4 ~ 200V					
Load OFF Voltage	0 ~ 100V				0 ~ 200V					
Power Consumption	3700Wmax		600 Wmax		1000Wmax		1450Wmax		1900Wmax	
Operating Temperature ²	0~40°C									
Dimension (HxWxD)	1509x647x766mm		573x647x766mm		573x647x766mm		728x647x766mm		885x647x766mm	
HxWxD (Not included wheels)	1405x647x766mm		469x647x766mm		469x647x766mm		625x647x766mm		781x647x766mm	
Weight	430 kg		100 kg		130 kg		170 kg		220 kg	
Safety & EMC	CE									

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz
 ② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面： 選購配件：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card



規 格

MODEL	34325A		34330A		34335A		34340A	
Power	25KW		30KW		35KW		40KW	
Current	0 ~ 25A	0 ~ 250A	0 ~ 30A	0 ~ 300A	0 ~ 35A	0 ~ 350A	0 ~ 40A	0 ~ 400A
Voltage	0 ~ 1000V							
Min. Operating Voltage	10V @ 250A		10V @ 300A		10V @ 350A		10V @ 400A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	104%							
Over Temp Protection (OTP)	Yes							
Constant Current Mode								
Range ¹	25A	250A	30A	300A	35A	350A	40A	400A
Resolution	0.4mA	4mA	0.48mA	4.8mA	0.56mA	5.6mA	0.64mA	6.4mA
Accuracy	± (0.1% of Setting + 0.2% of Range)							
Constant Resistance Mode								
Range	4800Ω~4Ω	4Ω~0.04008Ω	3999.6Ω~3.333Ω	3.333Ω~0.033396Ω	3428.4Ω~2.857Ω	2.857Ω~0.0286266Ω	3000Ω~2.5Ω	2.5Ω~0.02505Ω
Resolution	4.166μS	0.0668mΩ	5μS	0.05566mΩ	5.833μS	0.047711mΩ	6.66μS	0.04175mΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	10 ~ 1000V							
Resolution	16mV							
Accuracy	± 0.05% of (Setting + Range)							
Constant Power Mode								
Range	2500W	25000W	3000W	30000W	3500W	35000W	4000W	40000W
Resolution	40mV	400mW	48mV	480mW	56mV	560mW	64mV	640mW
Accuracy	± 0.5% of (Setting + Range)							
Constant Voltage Mode + Constant Current Mode								
Range	1000V	250A	1000V	300A	1000V	350A	1000V	400A
Resolution	16mV	4mA	16mV	4.8mA	16mV	5.6mA	16mV	6.4mA
Accuracy	± 1% of (Setting + Range)							
Constant Voltage Mode + Constant Power Mode								
Range	1000V	25000W	1000V	30000W	1000V	35000W	1000V	40000W
Resolution	16mV	400mW	16mV	480mW	16mV	560mW	16mV	640mW
Accuracy	± 1.0% of (Setting + Range)							
MPPT Mode								
Algorithm	P&O + Scanning							
Load mode	CC, CR, CV (MPPT C, R, V)							
Sampling interval	10ms~2000ms ; resolution 1ms							
P&O interval	10ms~2000ms ; resolution 1ms							
Memory situation	Discard old data and keep catching new data							
Dynamic Mode								
Timing								
Thigh & Tlow	0.050~9.999 / 99.99 / 999.9 / 9999ms							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.02A~1.25A/μs	0.2A~12.5A/μs	0.024A~1.5A/μs	0.24A~15A/μs	0.028A~1.75A/μs	0.28A~17.5A/μs	0.032A~2A/μs	0.32A~20A/μs
Resolution	0.005A/μs	0.05A/μs	0.006A/μs	0.06A/μs	0.007A/μs	0.07A/μs	0.008A/μs	0.08A/μs
Min. Rise Time	20μs(typical)							
Current								
Range	0~25A	25~250A	0~30A	30~300A	0~35A	35~350A	0~40A	40~400A
Resolution	0.4mA	4mA	0.48mA	4.8mA	0.56mA	5.6mA	0.64mA	6.4mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V	0~100V	100~1000V
Resolution	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV	1.6mV	16mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~25A	25~250A	0~30A	30~300A	0~35A	35~350A	0~40A	40~400A
Resolution	0.4mA	4mA	0.48mA	4.8mA	0.56mA	5.6mA	0.64mA	6.4mA
Accuracy	±0.1% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	10000W	25000W	10000W	30000W	10000W	35000W	10000W	40000W
Resolution	0.1W	1W	0.1W	1W	0.1W	1W	0.1W	1W
Accuracy	±0.125% of (Reading + Range)							
General								
Short Circuit								
Current	250A		300A		350A		400A	
Load ON Voltage	10.4 ~ 200V							
Load OFF Voltage	0 ~ 200V							
Power Consumption	2350 Wmax		2800Wmax		3250Wmax		3700Wmax	
Operating Temperature ²	0~40°C							
Dimension (HxWxD)	1041x647x766mm		1197x647x766mm		1353x647x766mm		1509x647x766mm	
HxWxD (Not included wheels)	937x647x766mm		1093x647x766mm		1249x647x766mm		1405x647x766mm	
Weight	280 kg		340 kg		390 kg		430 kg	
Safety & EMC	CE							

冷卻方式：智慧型風扇冷卻

輸入電源：① Load-20KW內(含)：100~230 Vac ±10%，50/60Hz
 ② Load-25KW以上(含)：200~230 Vac ±10%，50/60Hz

註*1:CC Mode 可強制於range II

註*2:操作溫度範圍為0~40°C，此規格表內之精確度僅適用於25°C±5°C

訂 購 方 式

選購介面： 選購配件：

- ① GPIB Card
- ② RS232 Card
- ③ USB Card
- ④ LAN Card

