

34000C 系列

超高功率直流电子负载



HIGH POWER DC ELECTRONIC LOAD



博计电子股份有限公司

236 新北市土城区中兴路7-1号

TEL : 886-2-2918-2620

FAX : 886-2-2912-9870

<http://www.prodigit.com.tw>

E-mail : pdsales@prodigit.com.tw



150V
600V
1200V6kW~
24kW

24机种



特 性

- 最大功率可达 192KW
- 最高达 8 台主/从并联控制
- 5位数之数位电压、电流以及功率表
- 高速量测及通讯传输速率
- 大型 LCD Display、可用飞梭旋钮或按键调整设定值
- 可同时显示电压值、电流值、瓦特值
- 适用于功率因数调整器(PFC)测试用 (600V,1200V机种)
- 可自动执行OCP、OPP测试
- 可设定开机状态值
- 于短路测试时可设定短路时间
- 定电流、定电阻、定电压、定功率、定电流 + 定电压、定功率 + 定电压、动态及短路模式
- 过电流、功率、温度保护及过电压示警
- 电压极性显示可设成正值 ("+") 或负值 ("- ")
- 支援太阳能板MPPT 测试
- 可选用介面： GPIB、RS232、USB、LAN
- 内建缓启动电路功能，允许UUT电源直接连接到342xC、343xC系列负载输入端，不再需要外接缓启动电路的大型继电器开关

说 明

- 34000C系列具有独立的控制及显示面板、定电流/定电阻/定电压/定功率/动态模式，配合面板上的150组 储存/呼叫 记忆，能有效地控制所有负载的设定，更可透过RS232、Ethernet、USB和GPIB等介面进行远端控制。
- 具备短路测试功能及设定短路时间，并可量测短路电压及电流。
- 在定电流及定功率模式下，可做动态负载之模拟，其电流上升、下降斜率均为独立可调，另具有-外部输入任意波形之动态负载功能。
- 具有OCP、OPP单键测试功能，使得OCP、OPP之测试更有效率及准确。
- 可设定的吃载/停止吃载 (LOAD ON/OFF) 电压点及良/不良 (GO/NG) 的比较判断功能、电压极性显示可正可负及150组 储存/呼叫 记忆，使得负载更适用于各种不同的应用。
- 多达150组测试参数及状态的储存功能，让其可根据自动测试 (auto sequence) 需求，随时将储存记忆调出来任意使用。
- 因其耐压可高达1200V，故而非常适用于功率因数调整器 (PFC) 的测试应用。
- 主/从控制最多为1个MASTER，7个SLAVE

应 用

- 电压/电流源测试
- 交换式电源供应器暂态响应
- 定电压模式供限流测试及模拟电池
- 电池放电
- 电池充电
- 研发、品管
- ATE系统
- 生产测试

规格								
MODEL	34106C		34108C		34110C		34112C	
Power ^{*1}	6KW		8KW		10KW		12KW	
Current	0 ~ 60A	0 ~ 600A	0 ~ 80A	0 ~ 800A	0 ~ 100A	0 ~ 1000A	0 ~ 120A	0 ~ 1200A
Voltage	0 ~ 150V							
Min. Operating Voltage	0.7V @ 600A		0.7V @ 800A		0.7V @ 1000A		0.7V @ 1200A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	105%							
Over Temp Protection (OTP)	90℃±5℃							
Constant Current Mode								
Range ^{*2}	60A	600A	80A	800A	100A	1000A	120A	1200A
Resolution	0.96mA	9.6mA	1.28mA	12.8mA	1.6mA	16mA	1.92mA	19.2mA
Accuracy ^{*3}	± 0.05% of (Setting + Range)							
Constant Resistance Mode								
Range	15000Ω~0.25Ω	0.25Ω~0.0012Ω	11250Ω~0.1875Ω	0.1875Ω~0.0009Ω	9000Ω~0.15Ω	0.15Ω~0.0007Ω	7500Ω~0.125Ω	0.125Ω~0.0006Ω
Resolution	66.666μS	4.167μΩ	88.888μS	3.125μΩ	111.111μS	2.5μΩ	133.333μS	2.084μΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	150V							
Resolution	2.5mV							
Accuracy	± 0.025% of (Setting + Range)							
Constant Power Mode								
Range	600W	6000W	800W	8000W	1000W	10000W	1200W	12000W
Resolution	9.6mW	96mW	12.8mW	128mW	16mW	160mW	19.2mW	192mW
Accuracy	± 0.1% of (Setting+Range)							
Short / OCP / OPP Test Function								
Short Time	100ms~10 Sec. or Continue							
Meas. Accuracy	NA							
OCP Time(Tstep)	100mS							
Meas. Accuracy	NA							
OPP Time(Tstep)	100mS							
Meas. Accuracy	NA							
Constant Voltage + Current Limit Mode								
Range	150V	600A	150V	800A	150V	1000A	150V	1200A
Resolution	2.5mV	9.6mA	2.5mV	12.8mA	2.5mV	3.2mA	2.5mV	19.2mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode								
Range	150V	6000W	150V	8000W	150V	10000W	150V	12000W
Resolution	2.5mV	96mW	2.5mV	128mW	2.5mV	160mW	2.5mV	192mW
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Surge Test								
Surge & Normal current	0~600A		0~800A		0~1000A		0~1200A	
Surge time	10~1000ms		10~1000ms		10~1000ms		10~1000ms	
Surge step	1~5							
MPPT Mode								
Algorithm	P&O							
Load mode	CV							
P&O interval	1000ms~60000ms ; resolution 1000ms							
Dynamic Mode								
Timing								
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.0144A~0.9A/μs	0.144A~9A/μs	0.0192A~1.2A/μs	0.192A~12A/μs	0.024A~1.5A/μs	0.24A~15A/μs	0.0288A~1.8A/μs	0.288A~18A/μs
Resolution	0.0036A/μs	0.036A/μs	0.0048A/μs	0.048A/μs	0.006A/μs	0.06A/μs	0.0072A/μs	0.072A/μs
Min. Rise Time	66.7μs(typical)							
Accuracy	± (5% of Setting) ±10μs							
Current								
Range	0~60A	60~600A	0~80A	80~800A	0~100A	100~1000A	0~120A	120~1200A
Resolution	0.96mA	9.6mA	1.28mA	12.8mA	1.6mA	16mA	1.92mA	19.2mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~15V	15~150V	0~15V	15~150V	0~15V	15~150V	0~15V	15~150V
Resolution	0.25mV	2.5mV	0.25mV	2.5mV	0.25mV	2.5mV	0.25mV	2.5mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~60A	60~600A	0~80A	80~800A	0~100A	100~1000A	0~120A	120~1200A
Resolution	0.96mA	9.6mA	1.28mA	12.8mA	1.6mA	16mA	1.92mA	19.2mA
Accuracy	±0.05% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	6000W		8000W		10000W		12000W	
Accuracy	± 0.06% of (Reading + Range)							
General								
Typical Short Resistance	0.0012Ω		0.0009Ω		0.0007Ω		0.0006Ω	
Maximum Short Current	600A		800A		1000A		1200A	
Load ON Voltage	0.25 ~ 62.5V							
Load OFF Voltage	0 ~ 62.5V							
Power Consumption	510VA		920VA		920VA		920VA	
Dimension (HxWxD)	446x444x763mm		572x444x763mm		572x444x763mm		572x444x763mm	
HxWxD (Not included wheels)	342x444x763mm		468x444x763mm		468x444x763mm		468x444x763mm	
Weight	62 kg		77.5 kg		84.8 kg		92 kg	
Temperature ^{*4}	0~40℃							
Safety & EMC								
CE								

冷却方式：智慧型风扇冷却

输入电源：100~230 Vac ±10% · 50/60Hz

注*1：功率规格仅适用于室温25℃

注*2：CC Mode 可强制于rangeII

注*3：当操作电流低于range 0.1%, accuracy为0.1% F.S.

注*4：Power F.S. = Vrange F.S. x Irange F.S.

注*5：操作温度范围为0~40℃ · 此规格表内之精确度仅适用于25℃±5℃

订购方式

选购配件：

选购介面： ❶ GPIB Card ❷ RS232 Card ❸ USB Card ❹ LAN Card

- ❶ 吊环
- ❷ 机架配件

- ❸ 把手
- ❹ 移除轮子

34106C 150V · 600A · 6KW

34108C 150V · 800A · 8KW

34110C 150V · 1000A · 10KW

34112C 150V · 1200A · 12KW

规格								
MODEL	34115C		34118C		34120C		34124C	
Power ^{*1}	15KW		18KW		20KW		24KW	
Current	0 ~ 150A	0 ~ 1500A	0 ~ 180A	0 ~ 1800A	0 ~ 200A	0 ~ 2000A	0 ~ 200A	0 ~ 2000A
Voltage	0 ~ 150V							
Min. Operating Voltage	0.7V @ 1500A		0.7V @ 1800A		0.7V @ 2000A		0.7V @ 2000A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	105%							
Over Temp Protection (OTP)	90°C±5°C							
Constant Current Mode								
Range ^{*2}	150A	1500A	180A	1800A	200A	2000A	200A	2000A
Resolution	2.4mA	24mA	2.88mA	28.8mA	3.2mA	32mA	3.2mA	32mA
Accuracy ^{*3}	± 0.05% of (Setting + Range)							
Constant Resistance Mode								
Range	6000Ω~0.1Ω	0.1Ω~0.0005Ω	5000Ω~0.0833Ω	0.0833Ω~0.0004Ω	4500Ω~0.075Ω	0.075Ω~0.0004Ω	4500Ω~0.075Ω	0.075Ω~0.0004Ω
Resolution	166.666μS	1.667μΩ	200μS	1.389μΩ	222.22μS	1.25μΩ	222.22μS	1.25μΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	150V							
Resolution	2.5mV							
Accuracy	± 0.025% of (Setting + Range)							
Constant Power Mode								
Range	1500W	15000W	1800W	18000W	2000W	20000W	2400W	24000W
Resolution	24mW	240mW	28.8mW	288mW	32mW	320mW	38.4mW	384mW
Accuracy	± 0.1% of (Setting+Range)							
Short / OCP / OPP Test Function								
Short Time	100ms~10 Sec. or Continue							
Meas. Accuracy	NA							
OCP Time(Tstep)	100mS							
Meas. Accuracy	NA							
OPP Time(Tstep)	100mS							
Meas. Accuracy	NA							
Constant Voltage + Current Limit Mode								
Range	150V	1500A	150V	1800A	150V	2000A	150V	2000A
Resolution	2.5mV	24mA	2.5mV	28.8mA	2.5mV	32mA	2.5mV	32mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode								
Range	150V	15000W	150V	18000W	150V	20000W	150V	24000W
Resolution	2.5mV	240mW	2.5mV	288mW	2.5mV	320mW	2.5mV	384mW
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Surge Test								
Surge & Normal current	0~1500A		0~1800A		0~2000A		0~2000A	
Surge time	10~1000ms		10~1000ms		10~1000ms		10~1000ms	
Surge step	1~5							
MPPT Mode								
Algorithm	P&O							
Load mode	CV							
P&O interval	1000ms~60000ms ; resolution 1000ms							
Dynamic Mode								
Timing								
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.036A~2.25A/μs	0.360A~22.5A/μs	0.0432A~2.7A/μs	0.432A~27A/μs	0.048A~3A/μs	0.48A~30A/μs	0.048A~3A/μs	0.48A~30A/μs
Resolution	0.009A/μs	0.09A/μs	0.0108A/μs	0.108A/μs	0.012A/μs	0.12A/μs	0.012A/μs	0.12A/μs
Min. Rise Time	66.7μs(typical)							
Accuracy	± (5% of Setting) ± 10μs							
Current								
Range	0~150A	150~1500A	0~180A	180~1800A	0~200A	200~2000A	0~200A	200~2000A
Resolution	2.4mA	24mA	2.88mA	28.8mA	3.2mA	32mA	3.2mA	32mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~15V	15~150V	0~15V	15~150V	0~15V	15~150V	0~15V	15~150V
Resolution	0.25mV	2.5mV	0.25mV	2.5mV	0.25mV	2.5mV	0.25mV	2.5mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~150A	15~1500A	0~180A	180~1800A	0~200A	200~2000A	0~200A	200~2000A
Resolution	2.4mA	24mA	2.88mA	28.8mA	3.2mA	32mA	3.2mA	32mA
Accuracy	± 0.05% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	15000W		18000W		20000W		24000W	
Accuracy	± 0.06% of (Reading + Range)							
General								
Typical Short Resistance	0.0005Ω		0.0004Ω		0.0004Ω		0.0004Ω	
Maximum Short Current	1500A		1320A		2000A		2000A	
Load ON Voltage	0.25 ~ 62.5V							
Load OFF Voltage	0 ~ 62.5V							
Power Consumption	1320VA		1320VA		1700VA		1700VA	
Dimension (HxWxD)	761x444x763mm		761x444x763mm		887x444x763mm		887x444x763mm	
HxWxD (Not included wheels)	657x444x763mm		657x444x763mm		783x444x763mm		783x444x763mm	
Weight	116.5 kg		124 kg		140.5 kg		155 kg	
Temperature ^{*4}	0~40°C							
Safety & EMC								
CE								

冷却方式：智慧型风扇冷却

输入电源：100~230 Vac ±10% · 50/60Hz

注*1：功率规格仅适用于室温25℃

注*2：CC Mode 可强制于rangeII

注*3：当操作电流低于range 0.1%, accuracy为0.1% F.S.

注*4：Power F.S. = Vrange F.S. x Irange F.S.

注*5：操作温度范围为0~40℃ · 此规格表内之精度仅适用于25℃±5℃

订购配件：

选购介面：

1 吊环

2 机架配件

3 把手

4 移除轮子



34115C 150V · 1500A · 15KW


34118C 150V · 1800A · 18KW

34120C 150V · 2000A · 20KW


34124C 150V · 2000A · 24KW

All specifications are subject to change without notice.


03




34106C




34108C




34110C




34112C




34115C



34118C



34120C



34124C

规格								
MODEL	34206C		34208C		34210C		34212C	
Power ^{*1}	6KW		8KW		10KW		12KW	
Current	0 ~ 42A	0 ~ 420A	0 ~ 56A	0 ~ 560A	0 ~ 70A	0 ~ 700A	0 ~ 84A	0 ~ 840A
Voltage	0 ~ 600V							
Min. Operating Voltage	10V @ 420A		10V @ 560A		10V @ 700A		10V @ 840A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	105%							
Over Temp Protection (OTP)	90℃±5℃							
Constant Current Mode								
Range ^{*2}	42A	420A	56A	560A	70A	700A	84A	840A
Resolution	0.672mA	6.72mA	0.896mA	8.96mA	1.12mA	11.2mA	1.334mA	13.44mA
Accuracy ^{*3}	± 0.05% of (Setting + Range)							
Constant Resistance Mode								
Range	85712Ω~1.42853Ω	1.42853Ω~0.02384Ω	64284Ω~1.0714Ω	1.0714Ω~0.01788Ω	51427.2Ω~0.85712Ω	0.85712Ω~0.014304Ω	42856Ω~0.714267Ω	0.714267Ω~0.01192Ω
Resolution	11.6669μS	23.84μΩ	15.5559μS	17.88μΩ	19.4449μS	14.304μΩ	23.3339μS	11.92μΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	600V							
Resolution	10mV							
Accuracy	± 0.025% of (Setting + Range)							
Constant Power Mode								
Range	600W	6000W	800W	8000W	1000W	10000W	1200W	12000W
Resolution	9.6mW	96mW	12.8mW	128mW	16mW	160mW	19.2mW	192mW
Accuracy	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)
Short / OCP / OPP Test Function								
Short Time	100ms~10 Sec. or Continue							
Meas. Accuracy	NA							
OCP Time(Tstep)	100mS							
Meas. Accuracy	NA							
OPP Time(Tstep)	100mS							
Meas. Accuracy	NA							
Constant Voltage + Current Limit Mode								
Range	600V	420A	600V	560A	600V	700A	600V	840A
Resolution	10mV	6.72mA	10mV	8.96mA	10mV	11.2mA	10mV	13.44mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode								
Range	600V	6000W	600V	8000W	600V	10000W	600V	12000W
Resolution	10mV	96mW	10mV	128mW	10mV	160mW	10mV	192mW
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Surge Test								
Surge & Normal current	0~420A		0~560A		0~700A		0~840A	
Surge time	10~1000ms		10~1000ms		10~1000ms		10~1000ms	
Surge step	1~5							
MPPT Mode								
Algorithm	P&O							
Load mode	CV							
P&O interval	1000ms~60000ms ; resolution 1000ms							
Dynamic Mode								
Timing								
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.0288~1.8A/μs	0.288A~18A/μs	0.0288A~1.8A/μs	0.288A~18A/μs	0.0336A~2.1A/μs	0.336A~21A/μs	0.0384A~2.4/μs	0.384A~24A/μs
Resolution	0.0072A/μs	0.072A/μs	0.0072A/μs	0.072A/μs	0.0084A/μs	0.084A/μs	0.0096A/μs	0.096A/μs
Accuracy	± (5% of Setting) ±10μs							
Current								
Range	0~42A	42~420A	0~56A	56~560A	0~70A	70~700A	0~84A	84~840A
Resolution	0.672mA	6.72mA	0.896mA	8.96mA	1.12mA	11.2mA	1.334mA	13.34mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V
Resolution	1mV	10mV	1mV	10mV	1mV	10mV	1mV	10mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~42A	42~420A	0~56A	56~560A	0~70A	70~700A	0~84A	84~840A
Resolution	0.672mA	6.72mA	0.896mA	8.96mA	1.12mA	11.2mA	1.334mA	13.34mA
Accuracy	±0.05% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	6000W		8000W		10000W		12000W	
Accuracy	± 0.06% of (Reading + Range)							
General								
Typical Short Resistance	0.0239Ω		0.0179Ω		0.0143Ω		0.00120Ω	
Maximum Short Current	420A		560A		700A		840A	
Load ON Voltage	0.4 ~ 100V							
Load OFF Voltage	0 ~ 100V							
Power Consumption	510VA		920VA		920VA		920VA	
Dimension (HxWxD)	446x444x763mm		572x444x763mm		572x444x763mm		572x444x763mm	
HxWxD (Not included wheels)	342x444x763mm		468x444x763mm		468x444x763mm		468x444x763mm	
Weight	62 kg		77.5 kg		84.8 kg		92 kg	
Temperature ^{*4}	0~40℃							
Safety & EMC CE								

冷却方式：智慧型风扇冷却

输入电源：100~230 Vac ±10% · 50/60Hz

注*1：功率规格仅适用于室温25℃

注*2：CC Mode 可强制于rangeⅡ

注*3：当操作电流低于range 0.1%, accuracy为0.1% F.S.

注*4：Power F.S. = Vrange F.S. x Irange F.S.

注*5：操作温度范围为0~40℃ · 此规格表内之精确度仅适用于25℃±5℃

订购方式

选购配件：

选购介面：❶ GPIB Card❷ RS232 Card❸ USB Card❹ LAN Card

❶ 吊环



x4

❷ 机架配件



❸ 把手



❹ 移除轮子





34206C 600V , 420A , 6KW



34208C 600V , 560A , 8KW



34210C 600V , 700A , 10KW



34212C 600V , 840A , 12KW

规格

规格								
MODEL	34215C		34218C		34220C		34224C	
Power ^{*1}	15KW		18KW		20KW		24KW	
Current	0 ~ 105A	0 ~ 1050A	0 ~ 126A	0 ~ 1260A	0 ~ 140A	0 ~ 1400A	0 ~ 168A	0 ~ 1680A
Voltage	0 ~ 600V							
Min. Operating Voltage	10V @ 1050A		10V @ 1260A		10V @ 1400A		10V @ 1680A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	105%							
Over Temp Protection (OTP)	90℃±5℃							
Constant Current Mode								
Range ^{*2}	105A	1050A	126A	1260A	140A	1400A	168A	1680A
Resolution	1.68mA	16.8mA	2.016mA	20.16mA	2.24mA	22.4mA	2.688mA	26.88mA
Accuracy ^{*3}	± 0.05% of (Setting + Range)							
Constant Resistance Mode								
Range	34284.8~0.571413Ω	0.571413~0.009536Ω	28570.67~0.476178Ω	0.476178~0.007947Ω	25713.6~0.42856Ω	0.42856~0.007152Ω	21428~0.357133Ω	0.357133~0.00596Ω
Resolution	29.1674μS	9.536μΩ	35.0009μS	7.947μΩ	38.8899μS	7.152μΩ	46.6679μS	5.96μΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	600V							
Resolution	10mV							
Accuracy	± 0.025% of (Setting + Range)							
Constant Power Mode								
Range	1500W	15000W	1800W	18000W	2000W	20000W	2400W	24000W
Resolution	24mW	240mW	28.8mW	288mW	32mW	320mW	38.4mW	384mW
Accuracy	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)
Short / OCP / OPP Test Function								
Short Time	100ms~10 Sec. or Continue							
Meas. Accuracy	NA							
OCP Time(Tstep)	100mS							
Meas. Accuracy	NA							
OPP Time(Tstep)	100mS							
Meas. Accuracy	NA							
Constant Voltage + Current Limit Mode								
Range	600V	1050A	600V	1260A	600V	1400A	600V	1680A
Resolution	10mV	16.8mA	10mV	20.16mA	10mV	22.4mA	10mV	26.88mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode								
Range	600V	15000W	600V	18000W	600V	20000W	600V	24000W
Resolution	10mV	240mW	10mV	288mW	10mV	320mW	10mV	384mW
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Surge Test								
Surge & Normal current	0~1050A		0~1260A		0~1400A		0~1680A	
Surge time	10~1000ms		10~1000ms		10~1000ms		10~1000ms	
Surge step	1~5							
MPPT Mode								
Algorithm	P&O							
Load mode	CV							
P&O interval	1000ms~60000ms ; resolution 1000ms							
Dynamic Mode								
Timing								
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.0432A~2.7A/μs	0.432A~27A/μs	0.048A~3A/μs	0.48A~30A/μs	0.0528A~3.3A/μs	0.528A~33A/μs	0.0576A~3.6A/μs	0.576A~36A/μs
Resolution	0.0108A/μs	0.108A/μs	0.012A/μs	0.12A/μs	0.0132A/μs	0.132A/μs	0.0144A/μs	0.144A/μs
Accuracy	± (5% of Setting) ±10μs							
Current								
Range	0~105A	105~1050A	0~126A	126~1260A	0~140A	140~1400A	0~168A	168~1680A
Resolution	1.68mA	16.8mA	2.016mA	20.16mA	2.24mA	22.4mA	2.688mA	26.88mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V	0~60V	60~600V
Resolution	1mV	10mV	1mV	10mV	1mV	10mV	1mV	10mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~105A	105~1050A	0~126A	126~1260A	0~140A	140~1400A	0~168A	168~1680A
Resolution	1.68mA	16.8mA	2.016mA	20.16mA	2.24mA	22.4mA	2.688mA	26.88mA
Accuracy	± 0.05% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	15000W		18000W		20000W		24000W	
Accuracy	± 0.06% of (Reading + Range)							
General								
Typical Short Resistance	0.0096Ω		0.0080Ω		0.0072Ω		0.0060Ω	
Maximum Short Current	1050A		1260A		1400A		1680A	
Load ON Voltage	0.4 ~ 100V							
Load OFF Voltage	0 ~ 100V							
Power Consumption	1320VA		1320VA		1700VA		1700VA	
Dimension (HxWxD)	761x444x763mm		761x444x763mm		887x444x763mm		887x444x763mm	
HxWxD (Not included wheels)	657x444x763mm		657x444x763mm		783x444x763mm		783x444x763mm	
Weight	116.5 kg		124 kg		140.5 kg		155 kg	
Temperature ^{*4}	0~40℃							
Safety & EMC	CE							

冷却方式：智慧型风扇冷却
 输入电源：100~230 Vac ±10% · 50/60Hz

注*1：功率规格仅适用于室温25℃
 注*2：CC Mode 可强制于rangeⅡ

注*3：当操作电流低于range 0.1%, accuracy为0.1% F.S.
 注*4：Power F.S. = Vrange F.S. x Irange F.S.

注*5：操作温度范围为0~40℃ · 此规格表内之
 精确度仅适用于25℃±5℃

订购方式

选购配件：

选购介面：
 ❶ GPIB Card
 ❷ RS232 Card
 ❸ USB Card
 ❹ LAN Card

❶ 吊环

❷ 机架配件

❸ 把手

❹ 移除轮子



34215C 600V, 1050A, 15KW




34218C 600V, 1260A, 18KW




34220C 600V, 1400A, 20KW




34224C 600V, 1680A, 24KW




34206C




34208C




34210C




34212C




34215C



34218C



34220C



34224C

规格

MODEL	34306C		34308C		34310C		34312C	
Power*1	6KW		8KW		10KW		12KW	
Current	0 ~ 24A	0 ~ 240A	0 ~ 32A	0 ~ 320A	0 ~ 40A	0 ~ 400A	0 ~ 48A	0 ~ 480A
Voltage	0 ~ 1200V							
Min. Operating Voltage	15V @ 240A		15V @ 320A		15V @ 400A		15V @ 480A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	104%							
Over Temp Protection (OTP)	90℃±5℃							
Constant Current Mode								
Range*2	24A	240A	32A	320A	40A	400A	48A	480A
Resolution	0.384mA	3.84mA	0.512mA	5.12mA	0.64mA	6.4mA	0.768mA	7.68mA
Accuracy*3	± 0.05% of (Setting + Range)							
Constant Resistance Mode								
Range	30KΩ~5Ω	5Ω~0.0625Ω	22.5KΩ~3.75Ω	3.75Ω~0.0468Ω	18KΩ~3Ω	3Ω~0.0375Ω	15KΩ~2.5Ω	2.5Ω~0.0312Ω
Resolution	3.333μS	83.334μΩ	4.444μS	62.5μΩ	5.5555μS	50μΩ	6.6666μS	41.667μΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	1200V							
Resolution	20mV							
Accuracy	± 0.025% of (Setting + Range)							
Constant Power Mode								
Range	600W	6000W	800W	8000W	1000W	10000W	1200W	12000W
Resolution	9.6mW	96mW	12.8mW	128mW	16mW	160mW	19.2mW	192mW
Accuracy	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)
Short / OCP / OPP Test Function								
Short Time	100ms~10 Sec. or Continue							
Meas. Accuracy	NA							
OCP Time(Tstep)	100mS							
Meas. Accuracy	NA							
OPP Time(Tstep)	100mS							
Meas. Accuracy	NA							
Constant Voltage + Current Limit Mode								
Range	1200V	240A	1200V	320A	1200V	400A	1200V	480A
Resolution	20mV	3.84mA	20mV	5.12mA	20mV	6.4mA	20mV	7.68mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode								
Range	1200V	6000W	1200V	8000W	1200V	10000W	1200V	12000W
Resolution	20mV	96mW	20mV	128mW	20mV	160mW	20mV	192mW
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Surge Test								
Surge & Normal current	0~240A		0~320A		0~400A		0~480A	
Surge time	10~1000ms		10~1000ms		10~1000ms		10~1000ms	
Surge step	1~5							
MPPT Mode								
Algorithm	P&O							
Load mode	CV							
P&O interval	1000ms~60000ms ; resolution 1000ms							
Dynamic Mode								
Timing								
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.0192A~1.2A/μs	0.192A~12A/μs	0.0192A~1.2A/μs	0.192A~12A/μs	0.0224A~1.4A/μs	0.224A~14A/μs	0.0256A~1.6A/μs	0.256A~16A/μs
Resolution	0.0048A/μs	0.048A/μs	0.0048A/μs	0.048A/μs	0.0056A/μs	0.056A/μs	0.0064A/μs	0.064A/μs
Accuracy	± (5% of Setting) ± 10μs							
Current								
Range	0~24A	24~240A	0~32A	32~320A	0~40A	40~400A	0~48A	48~480A
Resolution	0.384mA	3.84mA	0.512mA	5.12mA	0.64mA	6.4mA	0.768mA	7.68mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~120V	120~1200V	0~120V	120~1200V	0~120V	120~1200V	0~120V	120~1200V
Resolution	2mV	20mV	2mV	20mV	2mV	20mV	2mV	20mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~24A	24~240A	0~32A	32~320A	0~40A	40~400A	0~48A	48~480A
Resolution	0.384mA	3.84mA	0.512mA	5.12mA	0.64mA	6.4mA	0.768mA	7.68mA
Accuracy	±0.05% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	6000W		8000W		10000W		12000W	
Accuracy	± 0.06% of (Reading + Range)							
General								
Typical Short Resistance	0.0625Ω		0.0469Ω		0.0375Ω		0.0313Ω	
Maximum Short Current	240A		320A		400A		480A	
Load ON Voltage	0.96 ~ 240V							
Load OFF Voltage	0 ~ 240V							
Power Consumption	510VA		920VA		920VA		920VA	
Dimension (HxWxD)	446x444x763mm		572x444x763mm		572x444x763mm		572x444x763mm	
HxWxD (Not included wheels)	342x444x763mm		468x444x763mm		468x444x763mm		468x444x763mm	
Weight	62 kg		77.5 kg		84.8 kg		92 kg	
Temperature*4	0~40℃							
Safety & EMC	CE							

冷却方式：智慧型风扇冷却

输入电源：100~230 Vac ±10% · 50/60Hz

注*1：功率规格仅适用于室温25°C

注*2：CC Mode 可强制于rangeII

注*3：当操作电流低于range 0.1%, accuracy为0.1% F.S.

注*4：Power F.S. = Vrange F.S. x Irange F.S.

注*5：操作温度范围为0~40°C · 此规格表内之

精确度仅适用于25°C±5°C

订购方式

选购配件：

选购介面：① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card

① 吊环 ② 机架配件



③ 把手 ④ 移除轮子



③ 把手 ④ 移除轮子



34306C 1200V, 240A, 6KW



34308C 1200V, 320A, 8KW



34310C 1200V, 400A, 10KW



34312C 1200V, 480A, 12KW

规格								
MODEL	34315C		34318C		34320C		34324C	
Power ^{*1}	15KW		18KW		20KW		24KW	
Current	0 ~ 60A	0 ~ 600A	0 ~ 72A	0 ~ 720A	0 ~ 80A	0 ~ 800A	0 ~ 96A	0 ~ 960A
Voltage	0 ~ 1200V							
Min. Operating Voltage	15V @ 600A		15V @ 720A		15V @ 800A		15V @ 960A	
Protections								
Over Power Protection (OPP)	105%							
Over Current Protection (OCP)	104%							
Over Voltage Protection (OVP)	104%							
Over Temp Protection (OTP)	90℃±5℃							
Constant Current Mode								
Range ^{*2}	60A	600A	72A	720A	80A	800A	96A	960A
Resolution	0.96mA	9.6mA	1.152mA	11.52mA	1.28mA	12.8mA	1.536mA	15.36mA
Accuracy ^{*3}	± 0.05% of (Setting + Range)							
Constant Resistance Mode								
Range	12KΩ~2Ω	2Ω~ 0.0250Ω	10KΩ~1.666Ω	1.666Ω~0.0208Ω	9KΩ~1.5Ω	1.5Ω~0.0187Ω	7.5KΩ~1.25Ω	1.25Ω~0.0156Ω
Resolution	8.3333μS	33.334μΩ	10μS	27.778μΩ	11.111μS	25μΩ	13.333μS	20.834μΩ
Accuracy	±0.2% of (Setting + Range)							
Constant Voltage Mode								
Range	1200V							
Resolution	20mV							
Accuracy	± 0.025% of (Setting + Range)							
Constant Power Mode								
Range	1500W	15000W	1800W	18000W	2000W	20000W	2400W	24000W
Resolution	24mW	240mW	28.8mW	288mW	32mW	320mW	38.4mW	384mW
Accuracy	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)	± 0.2% of (Setting+Range)	± 0.1% of (Setting+Range)
Short / OCP / OPP Test Function								
Short Time	100ms~10 Sec. or Continue							
Meas. Accuracy	NA							
OCP Time(Tstep)	100mS							
Meas. Accuracy	NA							
OPP Time(Tstep)	100mS							
Meas. Accuracy	NA							
Constant Voltage + Current Limit Mode								
Range	1200V	600A	1200V	720A	1200V	800A	1200V	960A
Resolution	20mV	9.6mA	20mV	3.2mA	20mV	3.84mA	20mV	15.36mA
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Constant Voltage + Power Limit Mode								
Range	1200V	15000W	1200V	18000W	1200V	20000W	1200V	24000W
Resolution	20mV	240mW	20mV	288mW	20mV	320mW	20mV	384mW
Accuracy	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)	±0.05% of (Setting+Range)	±1.0% of (Setting+Range)
Surge Test								
Surge & Normal current	0~600A		0~720A		0~800A		0~960A	
Surge time	10~1000ms		10~1000ms		10~1000ms		10~1000ms	
Surge step	1~5							
MPPT Mode								
Algorithm	P&O							
Load mode	CV							
P&O interval	1000ms~60000ms ; resolution 1000ms							
Dynamic Mode								
Timing								
Thigh & Tlow	0.010~9.999 / 99.99 / 999.9 / 9999mS							
Resolution	0.001 / 0.01 / 0.1 / 1ms							
Accuracy	1μs / 10μs / 100μs / 1ms + 50ppm							
Slew Rate	0.0288A~1.8A/μs	0.288A~18A/μs	0.032A~2A/μs	0.32A~20A/μs	0.0352A~2.2A/μs	0.352A~22A/μs	0.0384A~2.4A/μs	0.384A~24A/μs
Resolution	0.0072A/μs	0.072A/μs	0.008A/μs	0.08A/μs	0.0088A/μs	0.088A/μs	0.0096A/μs	0.096A/μs
Accuracy	± (5% of Setting) ± 10μs							
Current								
Range	0~60A	60~600A	0~72A	72~720A	0~80A	80~800A	0~96A	96~960A
Resolution	0.96mA	9.6mA	1.152mA	11.52mA	1.28mA	12.8mA	1.536mA	15.36mA
Measurement								
Voltage Read Back								
Range (5 Digital)	0~120V	120~1200V	0~120V	120~1200V	0~120V	120~1200V	0~120V	120~1200V
Resolution	2mV	20mV	2mV	20mV	2mV	20mV	2mV	20mV
Accuracy	±0.025% of (Reading + Range)							
Current Read Back								
Range (5 Digital)	0~60A	60~600A	0~72A	72~720A	0~80A	80~800A	0~96A	96~960A
Resolution	0.96mA	9.6mA	1.152mA	11.52mA	1.28mA	12.8mA	1.536mA	15.36mA
Accuracy	±0.05% of (Reading + Range)							
Power Read Back								
Range (5 Digital)	15000W		18000W		20000W		24000W	
Accuracy	± 0.06% of (Reading + Range)							
General								
Typical Short Resistance	0.0250Ω		0.0209Ω		0.0188Ω		0.0157Ω	
Maximum Short Current	600A		720A		800A		960A	
Load ON Voltage	0.96 ~ 240V							
Load OFF Voltage	0 ~ 240V							
Power Consumption	1320VA		1320VA		1700VA		1700VA	
Dimension (HxWxD)	761x444x763mm		761x444x763mm		887x444x763mm		887x444x763mm	
HxWxD (Not included wheels)	657x444x763mm		657x444x763mm		783x444x763mm		783x444x763mm	
Weight	116.5 kg		124 kg		140.5 kg		155 kg	
Temperature ^{*4}	0~40℃							
Safety & EMC								
CE								

冷却方式：智慧型风扇冷却

输入电源：100~230 Vac ±10% · 50/60Hz

注*1：功率规格仅适用于室温25℃

注*2：CC Mode 可强制于rangeⅡ

注*3：当操作电流低于range 0.1%, accuracy为0.1% F.S.

注*4：Power F.S. = Vrange F.S. x Irange F.S.

注*5：操作温度范围为0~40℃ · 此规格表内之精确度仅适用于25℃±5℃

订购方式

选购配件：

① 吊环

② 机架配件

③ 把手

④ 移除轮子

选购介面：

① GPIB Card ② RS232 Card ③ USB Card ④ LAN Card

x4

















34315C 1200V · 600A · 15KW


34318C 1200V · 720A · 18KW

34320C 1200V · 800A · 20KW


34324C 1200V · 960A · 24KW




34306C




34308C




34310C




34312C




34315C



34318C



34320C



34324C